

Looser Bleibronze 80

Rohre	4.2
Rundstangen	4.4

Looser Bleibronze 82

Rohre	4.5
Rundstangen	4.6

Looser Bleibronze 85

Rohre	4.7
Rundstangen	4.8

Looser Lead Bronze 80

Tubes	4.2
Round bars	4.4


Looser Lead Bronze 82

Tubes	4.5
Round bars	4.6

Looser Lead Bronze 85

Tubes	4.7
Round bars	4.8





Rohre Tubes

Wir liefern zudem:

- abweichende Längen und Sägezuschnitte sowie Flachstangen im Format bis 212 x 502 x 3000 mm
- geschleuderte Ringe und Flanschbüchsen auf die Rohmasse oder Konturen vorgedreht
- einbaufertige Teile gemäss Zeichnung

Herstellart: Strang- oder Schleuderguss

Toleranz innen (Richtwert): 0/-1,0 mm

Toleranz aussen (Richtwert): 0/+1,0 mm

Weitere Werkstoffinformationen Register 7, Seiten 31 + 32.

* kurzfristig lieferbar

We also supply:

- different lengths and saw cuts as well as flat bars in format up to 212 x 502 x 3000 mm
- centrifuged rings and flange bushings pre-turned to the rough sizes
- ready-to-install parts in accordance with customer drawing

Manufacturing method: continuous or centrifugal casting

Tolerances inside (guideline value): 0/-1,0 mm

Tolerances outside (guideline value): 0/+1,0 mm

Additional material informations register 7, pages 31 + 32.


* available at short notice

Fertigmasse Final dimensions [d/D mm]	Liefermasse Delivery dimensions [d/D mm]	Länge Length [mm]	Gewicht Weight ca. / approx. [kg/m]	Artikelnummer Article number
15/30	14/31	3000	5,7	80R.014.031*
20/50	18/52	3000	17,2	80R.018.052*
25/35	24/36	3000	5,3	80.1.024.036
25/40	24/41	3000	8,0	80.1.024.041
25/60	23/62	3000	24,0	80R.023.062*
25/70	23/72	3000	34,2	80R.023.072*
30/45	29/46	3000	9,3	80.1.029.046
30/50	29/51	3000	12,8	80.1.029.051
30/60	28/62	3000	22,1	80R.028.062*
30/70	28/72	3000	32,4	80R.028.072*
30/80	28/82	3000	43,6	80R.028.082*
30/90	28/92	3000	56,1	80R.028.092*
35/45	33/47	3000	8,1	80.1.033.047
35/65	34/66	3000	23,1	80R.034.066*
35/70	33/72	630	29,7	80.1.033.072.630
40/50	38/52	3000	9,1	80.1.038.052
40/60	38/62	3000	17,4	80.1.038.062
40/70	38/72	3000	27,2	80.1.038.072
40/80	38/82	3000	39,0	80R.038.082*
40/90	38/92	3000	51,5	80R.038.092*
45/70	43/72	3000	24,1	80R.043.072*
45/75	43/77	3000	29,6	80.1.043.077
45/100	43/102	3000	61,8	80R.043.102*
45/110	43/112	3000	77,3	80R.043.112*
50/60	48/62	3000	11,2	80.1.048.062
50/70	48/72	3000	20,9	80.1.048.072
50/80	48/82	3000	32,1	80.1.048.082
50/110	48/112	3000	74,0	80R.048.112*
50/130	48/132	3000	110,6	80R.048.132*
60/70	58/72	3000	13,2	80R.058.072*
60/80	58/82	630	24,4	80.1.058.082.630
60/90	58/92	630	37,0	80.1.058.092.630
60/100	58/102	630	51,1	80.1.058.102.630
60/105	58/107	3000	60,1	80R.058.107*
60/150	58/152	3000	144,1	80R.058.152*
65/85	63/87	3000	26,0	80R.063.087*
70/80	68/82	3000	15,2	80R.068.082*
70/90	68/92	630	27,9	80.1.068.092.630
70/110	68/112	3000	57,2	80R.068.112*
70/120	68/122	3000	74,1	80R.068.122*
70/130	68/132	630	92,9	80.1.068.132.630
80/90	78/92	3000	17,2	80R.078.092*
80/110	78/112	3000	46,7	80R.078.112*
80/120	78/122	1000	63,9	80.1.078.122.1
80/130	78/132	3000	81,9	80R.078.132*
80/140	78/142	3000	103,8	80R.078.142*

Looser Bleibronze 80 (LBB 80) Looser Lead Bronze 80 (LBB 80)



Fertigmasse Final dimensions [d/D mm]	Liefermasse Delivery dimensions [d/D mm]	Länge Length [mm]	Gewicht Weight ca. / approx. [kg/m]	Artikelnummer Article number
90/120	88/122	3000	51,6	80R.088.122*
90/140	88/142	3000	89,7	80R.088.142*
90/160	88/162	3000	135,8	80R.088.162*
100/140	98/142	630	76,7	80.1.098.142.630
100/150	98/152	3000	97,5	80R.098.152*
100/160	98/162	3000	122,6	80R.098.162*
110/130	108/132	3000	41,6	80R.108.132*
110/160	108/162	630	105,8	80.1.108.162.630
120/150	118/152	3000	66,3	80R.118.152*
120/160	118/162	3000	89,0	80R.118.162*
140/170	138/172	3000	75,7	80.1.138.172
160/180	158/182	3000	59,0	80R.158.182*
170/228	168/230	1000	179,0	80.1.168.230.1
180/200	178/202	3000	65,9	80R.178.202*
226/280	224/282	1000	210,7	80.1.224.282.1



Rohre
Tubes

Wir liefern zudem:

- abweichende Längen und Sägezuschnitte sowie Flachstangen im Format bis 212 x 502 x 3000 mm
- geschleuderte Ringe und Flanschbüchsen auf die Rohmasse oder Konturen vorgedreht
- einbaufertige Teile gemäss Zeichnung

Herstellart: Strang- oder Schleuderguss

Toleranz innen (Richtwert):
0/-1,0 mm

Toleranz aussen (Richtwert):
0/+1,0 mm

Weitere Werkstoffinformationen
Register 7, Seiten 31 + 32.

* kurzfristig lieferbar

We also supply:

- different lengths and saw cuts as well as flat bars in format up to 212 x 502 x 3000 mm
- centrifuged rings and flange bushings pre-turned to the rough sizes
- ready-to-install parts in accordance with customer drawing


Manufacturing method: continuous or centrifugal casting

Tolerances inside
(guideline value): 0/-1,0 mm

Tolerances outside
(guideline value): 0/+1,0 mm

Additional material informations
register 7, pages 31 + 32.

* available at short notice



Rundstangen
Round bars

Wir liefern zudem:

- abweichende Längen und Sägezuschnitte sowie Flachstangen im Format bis 212 x 502 x 3000 mm
- geschleuderte Ringe und Flanschbüchsen auf die Rohmasse oder Konturen vorgedreht
- einbaufertige Teile gemäss Zeichnung

Herstellart: Strangguss

Toleranz (Richtwert):
0/+1,0 mm

Weitere Werkstoffinformationen
Register 7, Seiten 31 + 32.

* kurzfristig lieferbar

We also supply:

- different lengths and saw cuts as well as flat bars in format up to 212 x 502 x 3000 mm
- centrifuged rings and flange bushings pre-turned to the rough sizes
- ready-to-install parts in accordance with customer drawing

Manufacturing method: continuous casting

Tolerances (guideline value):
0/+1,0 mm

Additional material informations
register 7, pages 31 + 32.


* available at short notice

Fertigmasse Final dimensions [D mm]	Liefermasse Delivery dimensions [D mm]	Länge Length [mm]	Gewicht Weight ca. / approx. [kg/m]	Artikelnummer Article number
16	17	3000	2,0	80.2.017
18	19	3000	2,7	80S.019*
20	21	3000	3,2	80.2.021
25	26	3000	4,9	80.2.026
30	31	3000	7,0	80.2.031
35	36	3000	9,4	80.2.036
40	41	3000	12,2	80.2.041
45	46	3000	15,5	80S.046*
50	51	3000	18,9	80.2.051
60	61	3000	27,0	80.2.061
65	66	3000	31,7	80S.066*
70	71	630	36,6	80.2.071.630
75	76	3000	41,9	80S.076*
80	81	630	47,6	80.2.081.630
85	86	3000	53,6	80S.086*
90	91	630	60,1	80.2.091.630
100	102	630	75,5	80.2.102.630
110	112	3000	91,3	80S.112*
120	122	3000	108,1	80S.122*
130	132	3000	126,4	80S.132*
140	142	630	146,4	80.2.142.630
150	152	3000	167,3	80S.152*
160	162	3000	190,0	80S.162*

Looser Bleibronze 82 (LBB 82) Looser Lead Bronze 82 (LBB 82)



Fertigmasse Final dimensions [d/D mm]	Liefermasse Delivery dimensions [d/D mm]	Länge Length [mm]	Gewicht Weight ca. / approx. [kg/m]	Artikelnummer Article number
15/25	14/26	3000	3,4	82.1.014.026
15/35	14/36	3000	7,9	82.1.014.036
15/40	14/41	3000	10,7	82.1.014.041
20/35	19/36	3000	6,7	82.1.019.036
20/40	19/41	3000	9,5	82.1.019.041
25/35	24/36	3000	5,2	82.1.024.036
25/45	24/46	3000	11,1	82.1.024.046
30/40	29/41	3000	6,1	82.1.029.041
30/50	29/51	3000	12,6	82.1.029.051
30/55	29/56	3000	16,1	82.1.029.056
30/60	29/61	3000	20,7	82.1.029.061
35/50	34/51	3000	10,4	82.1.034.051
35/65	34/66	3000	23,0	82.1.034.066
35/70	34/71	3000	27,9	82.1.034.071
40/60	39/61	3000	15,8	82.1.039.061
40/80	39/81	3000	36,0	82R.039.081*
50/75	49/76	3000	24,9	82.1.049.076
60/85	58/86	3000	30,2	82.1.058.086
60/110	58/112	1000	66,0	82.1.058.112.1
70/95	68/96	3000	33,0	82.1.068.096
80/120	78/122	1000	63,2	82.1.078.122.1



Rohr Tubes

Wir liefern zudem:

- abweichende Längen und Sägezuschnitte sowie Flachstangen im Format bis 212 x 502 x 3000 mm
- geschleuderte Ringe und Flanschbüchsen auf die Rohmasse oder Konturen vorgedreht
- einbaufertige Teile gemäss Zeichnung

Herstellart: Strang- oder Schleuderguss

Toleranz innen (Richtwert):
0/-1,0 mm

Toleranz aussen (Richtwert):
0/+1,0 mm

Weitere Werkstoffinformationen
Register 7, Seiten 33 + 34.

* kurzfristig lieferbar

We also supply:

- different lengths and saw cuts as well as flat bars in format up to 212 x 502 x 3000 mm
- centrifuged rings and flange bushings pre-turned to the rough sizes
- ready-to-install parts in accordance with customer drawing


Manufacturing method: continuous or centrifugal casting

Tolerances inside
(guideline value): 0/-1,0 mm

Tolerances outside
(guideline value): 0/+1,0 mm

Additional material informations
register 7, pages 33 + 34.

* available at short notice



Rundstangen
Round bars

Fertigmasse Final dimensions [D mm]	Liefermasse Delivery dimensions [D mm]	Länge Length [mm]	Gewicht Weight ca. / approx. [kg/m]	Artikelnummer Article number
16	17	3000	2,0	82.2.017
20	21	3000	3,2	82.2.021
22	23	3000	3,8	82.2.023
25	26	3000	4,9	82.2.026
30	31	3000	7,0	82.2.031
35	36	3000	9,3	82.2.036
40	41	3000	12,1	82.2.041
45	46	3000	15,2	82.2.046
50	51	1000	18,7	82.2.051.1
55	56	1000	22,5	82.2.056.1
60	61	1000	26,7	82.2.061.1
70	71	1000	36,2	82.2.071.1
75	77	1000	42,6	82.2.077.1
80	81	1000	47,1	82.2.081.1
85	87	1000	54,3	82.2.087.1
90	91	1000	59,5	82.2.091.1
100	102	1000	74,7	82.2.102.1
110	112	1000	90,0	82.2.112.1
120	122	1000	107,0	82.2.122.1
150	152	1000	166,0	82.2.152.1

Wir liefern zudem:

- abweichende Längen und Sägezuschnitte sowie Flachstangen im Format bis 212 x 502 x 3000 mm
- geschleuderte Ringe und Flanschbüchsen auf die Rohmasse oder Konturen vorgedreht
- einbaufertige Teile gemäss Zeichnung

Herstellart: Strangguss

Toleranz (Richtwert):
0/+1,0 mm

Weitere Werkstoffinformationen
Register 7, Seiten 33 + 34.

We also supply:

- different lengths and saw cuts as well as flat bars in format up to 212 x 502 x 3000 mm
- centrifuged rings and flange bushings pre-turned to the rough sizes
- ready-to-install parts in accordance with customer drawing

Manufacturing method: continuous casting

Tolerances (guideline value):
0/+1,0 mm


Additional material informations
register 7, pages 33 + 34.

* available at short notice

Looser Bleibronze 85 (LBB 85) Looser Lead Bronze 85 (LBB 85)



Fertigmasse Final dimensions	Liefermasse Delivery dimensions	Länge Length	Gewicht Weight ca. / approx. [kg/m]	Artikelnummer Article number
[d/D mm]	[d/D mm]	[mm]		
27/43	25/45	500	10,5	85R.025.045.500*
100/120	98/122	3000	38,6	85.1.098.122



Rohre Tubes

Wir liefern zudem:

- abweichende Abmessungen und Sägezuschnitte
- einbaufertige Teile gemäss Zeichnung

Herstellart: Strangguss

Toleranz innen (Richtwert):
0/-1,0 mm

Toleranz aussen (Richtwert):
0/+1,0 mm

Weitere Werkstoffinformationen
Register 7, Seiten 35 + 36.

* kurzfristig lieferbar

We also supply:

- different lengths and saw cuts
- ready-to-install parts in accordance with customer drawing


Manufacturing method: continuous casting

Tolerances inside
(guideline value): 0/-1,0 mm

Tolerances outside
(guideline value): 0/+1,0 mm

Additional material informations
register 7, pages 35 + 36.

* available at short notice



Rundstangen
Round bars

Fertigmasse Final dimensions [D mm]	Liefermasse Delivery dimensions [D mm]	Länge Length [mm]	Gewicht Weight ca. / approx. [kg/m]	Artikelnummer Article number
20	21	3000	3,3	85.2.021
30	31	3000	7,1	85.2.031
40	41	3000	12,5	85.2.041
50	51	3000	19,3	85.2.051

Wir liefern zudem:

- abweichende Längen und Sägezuschnitte
- einbaufertige Teile gemäss Zeichnung

Herstellart: Strangguss

Toleranz (Richtwert):
 0/+1,0 mm

Weitere Werkstoffinformationen
 Register 7, Seiten 35 + 36.

We also supply:

- different lengths and saw cuts
- ready-to-install parts in accordance with customer drawing

Manufacturing method: continuous casting

Tolerances (guideline value):
 0/+1,0 mm

Additional material informations
 register 7, pages 35 + 36.

* available at short notice

Walter Looser AG
Bronzen und Gleitlager
Josefstrasse 206
CH-8005 Zürich

Technische Änderungen vorbehalten, alle Angaben ohne Gewähr.
 Subject to technical modifications; no responsibility is accepted for the accuracy of this information.